

# SAFETY DATA SHEET

## 1. Identification

Product number SP955  
Product identifier **MARTIN YALE STATIC ELIMINATOR**  
Revision date 08-01-2014  
Company information MARTIN YALE INDUSTRIES  
251 WEDCOR  
WABASH, IN 46992 United States  
Company phone 219-563-0641  
Emergency telephone US 1-866-836-8855  
Emergency telephone outside US 1-952-852-4646  
Version # 03  
Supersedes date 05-30-2014  
Recommended use Antistatic agent  
Recommended restrictions None known.

## 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1  
Health hazards Serious eye damage/eye irritation Category 2  
Environmental hazards Not classified.  
OSHA defined hazards Not classified.

### Label elements



Signal word Danger  
Hazard statement Extremely flammable aerosol. Causes serious eye irritation.  
Precautionary statement  
Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye/face protection.  
Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.  
Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Disposal Not available.  
Hazard(s) not otherwise classified (HNOC) None known.  
Supplemental information None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethyl Alcohol		64-17-5	60 - 80
1,1-Difluoroethane		75-37-6	20 - 40
Other components below reportable levels			0.1 - 1

#: This substance has workplace exposure limit(s).

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Product name: Multi-Purpose Anti-Static Spray

Product #: 955-003 Version #: 03 Revision date: 08-01-2014 Issue date: 04-23-2014

SDS US

1 / 10

Composition comments	The full text for all R-phrases is displayed in Section 16 of the SDS.
<b>4. First-aid measures</b>	
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Skin contact	For minor skin contact, avoid spreading material on unaffected skin.
Eye contact	Rinse with water.
Ingestion	If material is ingested, immediately contact a poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. No need for first aid is anticipated if material is swallowed.
Most important symptoms/effects, acute and delayed	Headache. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	In case of shortness of breath, give oxygen. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Keep victim under observation. Keep victim warm.
<b>5. Fire-fighting measures</b>	
Suitable extinguishing media	Powder. Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
<b>6. Accidental release measures</b>	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. After removal flush contaminated area thoroughly with water. This material and its container must be disposed of as hazardous waste.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only in area provided with appropriate exhaust ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Handle and open container with care. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Keep away from heat, sparks, and flame. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Level 2 Aerosol.

## 8. Exposure controls/personal protection

### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m <sup>3</sup> 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m <sup>3</sup> 1000 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1,1-Difluoroethane (CAS 75-37-6)	TWA	2700 mg/m <sup>3</sup> 1000 ppm

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Exposure guidelines

No Exposure standards allocated.

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

Do not get in eyes. When using do not smoke. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

Physical state	Gas.
Form	Aerosol.
Color	clear colorless
Odor	Characteristic.
Odor threshold	Not available.
pH	Not applicable estimated
Melting point/freezing point	Not available.
Initial boiling point and boiling range	134.9 °F (57.17 °C) estimated
Flash point	-58.0 °F (-50.0 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.

### Upper/lower flammability or explosive limits

Flammability limit - lower (%)	2.6 % estimated
Flammability limit - upper (%)	12.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.

Vapor pressure 27 - 37 psig @70F estimated

Vapor density Not available.

Relative density Not available.

### Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 856.4 °F (458 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

### Other information

Specific gravity 0.812 estimated

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Risk of ignition.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Ingestion Not available.

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation.

Information on toxicological effects

Acute toxicity Acute LC50: 157 mg/l/4h, Rat, Inhalation

Product	Species	Test Results
Multi-Purpose Anti-Static Spray (CAS Mixture)		
Acute Dermal LD50	Rabbit	21569.0332 mg/kg estimated 12712.2061 ml/kg estimated
	Rat	
Inhalation LC50	Cat	107.7317 mg/l, 4.5 Hours estimated 55.0956 mg/l, 6 Hours estimated
	Mouse	75680.8203 ppm estimated 100.1888 mg/l, 134 Minutes estimated 49.1925 mg/l, 4 Hours estimated 47.9312 mg/l, 24 Hours estimated
	Rat	220 %, 4 Hours estimated 157 mg/l/4h 146.1901 mg/l, 4 Hours estimated 64.7071 mg/l, 6 Hours estimated
Oral LD50	Guinea pig	7013.0894 mg/kg estimated
	Monkey	7568.082 mg/kg estimated
	Mouse	13244.1436 ml/kg estimated 4351.647 mg/kg estimated
	Rat	9838.5068 ml/kg estimated 9125 g/kg estimated
Other LD50	Mouse	7568.082 mg/kg estimated
	Rat	5133.6821 mg/kg estimated
Components	Species	Test Results
1,1-Difluoroethane (CAS 75-37-6)		
Acute Inhalation LC50	Rat	44 - 437500 %, 4 Hours
Ethyl Alcohol (CAS 64-17-5)		
Acute Inhalation LC50	Cat	85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm 79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours 51.3 mg/l, 6 Hours

Components	Species	Test Results
Oral LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Rat	7800 ml/kg
		7060 mg/kg
Other LD50	Mouse	6000 mg/kg
	Rat	4070 mg/kg

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Not expected to be hazardous by OSHA criteria.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	Not expected to be hazardous by OSHA criteria.
Carcinogenicity	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful.

## 12. Ecological information

Ecotoxicity LC50: 16191 mg/L, Fish, 96.00 Hours  
EC50: 14503 mg/L, Daphnia, 48.00 Hours

Product	Species	Test Results
Multi-Purpose Anti-Static Spray (CAS Mixture)		
Aquatic		
Algae	IC50	Algae 72 Hours
Crustacea	EC50	Daphnia 14503 mg/L, 48 Hours
Fish	LC50	Fish 16191 mg/L, 96 Hours
Components	Species	Test Results
Ethyl Alcohol (CAS 64-17-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 7700 - 11200 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) > 100.1 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Partition coefficient n-octanol / water (log Kow)	
1,1-Difluoroethane	0.75
Ethyl Alcohol	-0.31
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Product name: Multi-Purpose Anti-Static Spray

Product #: 955-003 Version #: 03 Revision date: 08-01-2014 Issue date: 04-23-2014

SDS US  
6 / 10

### 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	153, N82
Packaging exceptions	LTD QTY
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s) Packing	2.1
group Environmental	Not applicable.
hazards ERG Code	Yes
	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY

#### IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s) Packing	None
group Environmental	Not applicable.
hazards	
Marine pollutant	Yes
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions  
Transport in bulk according to  
Annex II of MARPOL 73/78 and  
the IBC Code

LTD QTY  
Not applicable.


DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

Product name: Multi-Purpose Anti-Static Spray

Product #: 955-003 Version #: 03 Revision date: 08-01-2014 Issue date: 04-23-2014

SDS US

8 / 10



SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
t-Butyl Alcohol	75-65-0	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-Difluoroethane (CAS 75-37-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

1,1-Difluoroethane (CAS 75-37-6)

Ethyl Alcohol (CAS 64-17-5)

US. New Jersey Worker and Community Right-to-Know Act

1,1-Difluoroethane (CAS 75-37-6)

Ethyl Alcohol (CAS 64-17-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl Alcohol (CAS 64-17-5)

US. Rhode Island RTK

1,1-Difluoroethane (CAS 75-37-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-23-2014

Revision date 08-01-2014

Version # 03

Disclaimer

Sprayway cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Product and Company Identification: Product Uses  
Hazard(s) identification: <INDENT>Prevention  
Composition / Information on Ingredients: Ingredients  
First-aid measures: Most important symptoms/effects, acute and delayed  
Fire-fighting measures: Specific methods  
Physical & Chemical Properties: Multiple Properties  
Physical and chemical properties: Appearance  
Toxicological information: Symptoms related to the physical, chemical and toxicological characteristics  
Transport Information: Material Transportation Information  
Regulatory Information: United States  
Other information, including date of preparation or last revision: Disclaimer  
GHS: Classification