

EZCreaser



Low- to medium-volume creasing, perforating and scoring


Top friction-feed operation


Automatic sheet set-up with a single touch


Supports perfect-bind covers

Rotary perf, optional micro-perf and score wheels available

Auto setups of all the following:








Get the features and speed you need, in an easy-to-use, affordable machine.







Rotary Perf and Score



Micro Lateral Adjustment

The COUNT™ EZCreaser gives you the robust features you need at an economical price, for lower to medium volume creasing, perforating and scoring. You get the speed and reliability of a top-feed automatic friction paper feeder, with smooth, consistent operation. You get a machine that's simple to set up, and easy for anyone to use with the popular COUNT touch-screen operation, and one-touch automatic set-ups built in. You get even higher speeds when operating in perf mode, with 5 interchangeable perf (including micro-perf) and score assembly options available.



EZCreaser

Count, MADE IN USA

An easy-to-use, affordable solution for low- to medium-volume creasing, perforating and scoring.

Features

- Offers a reliable top-load friction paper feed.
- · CAM actuated compression creasing.
- Automated distance recognition allows auto setups for your most common creases and corresponding folds, including perfect bind.
- · Comes standard with rotary perf wheel assembly.
- Optional micro-perf and score wheel assemblies are available.
- Includes micro-laterally adjustable feed rails and a sheet counter for batch and total counting.
- An ideal companion to the COUNT KF-200 for inline folding.
- Two-sided die creasing rod accommodates for heavier stock- simply remove and flip over to change from narrow to wide crease.
- User-friendly touch screen for easy set up and control of the machine.

Automatic Set-Up for Many Common Folds

Half

Tri-Fold

Z-Fold

Letter Fold

Roll Fold

Gate Fold

Double Gate Fold

Double Parallel Fold

Perfect Bind - No Hinge

Perfect Bind - Single Hinge

Perfect Bind - Double Hinge

Specifications

Model: EZCreaser

Model No.: EZCREASER

Paper Feed: Friction

Weight: 144 lbs (66 kg)

Max Compression Crease: 4,500

(sheets per hour)

Max Rotary Perf/Score Speed: 12,000

(sheets per hour)

Paper Weight Range: 60 - 350

(gsm)

Dimensions: 47.0 L x 29.0 W x 22.0 H in

(119.4 x 73.7 x 55.9 cm)

Max Sheet Size: 24.0 L x 18.0 W in (61.0 x 45.7 cm)

Min Sheet Size: 4.5 L x 4.5 W in (11.4 x 11.4 cm)

Electrical: 115 V, 60 Hz, 20 A or 230 V, 50 Hz, 20 A

Made in: U.S.A.



